

10/532962

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/046460 A1

(51) International Patent Classification⁷: **D21F 5/04**

(21) International Application Number:
PCT/FI2003/000891

(22) International Filing Date:
19 November 2003 (19.11.2003)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20022063 19 November 2002 (19.11.2002) FI

(71) Applicant (for all designated States except US): **METSO
PAPER, INC.** [FI/FI]; Fabianinkatu 9 A, FIN-00130
Helsinki (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LEIMU, Juha**


[FI/FI]; Tiilentekijäkatu 9 C, FIN-20810 Turku (FI).
KOMULAINEN, Antti [FI/FI]; Tarhiantie 22, FIN-42700
Keuruu (FI). **JUPPI, Kari** [FI/FI]; Iiiekkapohjantie
259, FIN-40270 Palokka (FI). **KURKI, Matti** [FI/FI];
Kariniementie 15, FIN-40520 Jyväskylä (FI). **SALMI-
NEN, Martti** [FI/FI]; Rautpohjankatu 3 B 48, FIN-40700
Jyväskylä (FI). **JOKINEN, Reijo** [FI/FI]; Kriivarinkuja 3,
FIN-21280 Raisio (FI).

(74) Agent: **TURUN PATENTTITOIMISTO OY**; P.O. Box
99, FIN-20521 Turku (FI).

(81) Designated States (*national*): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ,
CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE
(utility model), DE, DK (utility model), DK, DM, DZ, EC,
EE (utility model), EE, EG, ES, FI (utility model), FI, GB,
GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL,

[Continued on next page]

(54) Title: **SEALING ARRANGEMENT AGAINST A MOVING FABRIC**



(57) Abstract: The invention relates to a sealing arrangement (7) against a moving fabric (4b) in a paper machine or the like. The sealing arrangement includes a stiff sealing element (9) placed on the fabric's (4b) side on the entire width in connection with a paper sheet (4a) supported by the fabric (4b). The sealing element has been arranged on a support so that the location of the sealing element with respect to the fabric (4b) can be adjusted nearer to or, correspondingly, further from the fabric. As a sealing element there is at least a single-chambered labyrinth sealing (19).

WO 2004/046460 A1